

CHEMFIX CH+

Page: 1

Compilation date: 13/01/2012

Revision date: 12/12/2013

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CHEMFIX CH+

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A Chemical anchoring application

1.3. Details of the supplier of the safety data sheet

Company name: Chemfix Products Limited

Mill Street East

Dewsbury

West Yorkshire

WF12 9BQ

United Kingdom

Tel: +44 (0)1924 453886

Fax: +44 (0)1924 458995

Email: sds@chemfix.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1924 431679

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Aquatic Chronic 3: H412; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life

with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P264: Wash skin thoroughly after handling.

CHEMFIX CH+

Page: 2

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYLVINYLBENZENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
248-846-1	28106-30-1	-	Acute Tox. 4: H302+312+332; STOT SE 3: H335; Aquatic Chronic 2: H411;	3-10%
			Eye Irrit. 2: H319; Skin Irrit. 2: H315	

2-ETHYLHEXYL BENZOATE

226-641-8	5444-75-7	-	Aquatic Chronic 4: H413	1-3%	
			1		ı

POLY(OXY.1,2-ETHANDIYL),A,A'-[[(4-METHYLPHENYL)IMINO]DI-2,1-ETHANDIYL]BIS[OMEGA-HYDROXY-

	-	103671-44-9	-	Eye Dam. 1: H318; Acute Tox. 4: H302	1-3%
--	---	-------------	---	--------------------------------------	------

DIBENZOYL PEROXIDE - REACH registered number(s): 01-2119511472-50-XXXX

202-327-6	94-36-0	-	Skin Sens. 1: H317; Org. Perox. B:	1-3%
			H241; Eye Irrit. 2: H319	

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. - REACH registered number(s): 01-2119455851-35

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226;	<1%
			STOT SE 3: H335; Aquatic Chronic 2:	
			H411	

N,N-DIMETHYL-P-TOLUIDINE

202-805-4	99-97-8	-	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 3: H301; STOT RE 2: H373;	
			Aquatic Chronic 3: H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

CHEMFIX CH+

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: If conscious, give half a litre of water to drink immediately. Do not induce vomiting.

Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be loss of consciousness.Inhalation: There may be loss of consciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical

powder. Carbon dioxide. Foam. Do not use halons.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Sealed, heated containers can pressurise leading to explosion. In combustion emits

toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash the area with water.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Keep away from Heat and sources of ignition. Comp. B = Use non-sparking tools.

CHEMFIX CH+

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Ensure lighting and electrical equipment are not a source of ignition. Store in a cool, well

ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: * Breathing protection is required in inadequately ventilated places. Gas/vapour filter,

type A: organic vapours (EN141).

Hand protection: * Nitrile gloves. Viton gloves. Wear solvent proof gloves. Recommended thickness of

material >0.4 mm. As the product is a preperation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked

prior to the application.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Characteristic odour

Oxidising: Not applicable.

Solubility in water: Insoluble

Relative density: 1.61 VOC g/l: 0.66

CHEMFIX CH+

Page: 5

9.2. Other information

Other information: * Solid suspension - classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. May polymerise on heating.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Reducing agents. Acids. Alkali. Heavy metal compounds. Organic peroxide. Oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: If exposed to high temperatures it will emit hazardous fumes and smoke.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE

ORL	MUS	LD50	5700	mg/kg
ORL	RAT	LD50	7710	mg/kg

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
				5 5

N,N-DIMETHYL-P-TOLUIDINE

				,,
IPR	MUS	LD50	212	ma/ka
II IX	INIUS	LDJU	Z 1 Z	ilig/kg

Relevant hazards for substance:

Hazard	Poute	Racic
Hazard	Route	Basis

CHEMFIX CH+

Page: 6

Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be loss of consciousness.Inhalation: There may be loss of consciousness.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Small quantities of the product can be mixed and allowed to cure, then can be

disposed as solid waste.

Waste code number: 08 04 12

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

CHEMFIX CH+

Page: 7

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

MAL Code: 1-5

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H241: Heating may cause a fire or explosion.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

ENVIRONMENTAL CARE: Please do not dispose of uncured material. If disposing

please mix any waste product to its cured state.